



712 Flue Gas Analyzer

**New!
Five
Tools in
One!!**

The TPI 712 is an all in one instrument designed to maximize diagnostic efficiency and accuracy.

**Ask about
the optional
A740
Infrared
Printer.**



4.0" w x 8.12" h x 2.25" d

Five Tools in One!

1. Combustion Efficiency Analyzer

- Measure O₂ and CO
- Calculate CO₂, efficiency, excess air and ratio.
- Will work with high efficiency furnaces, hot water heaters, and other combustible gas appliances.

2. Combustible Gas Detector

- Set at 100 ppm sensitivity for natural gas

3. CO Analyzer

- Measure 0-10,000 ppm CO

4. Differential Thermometer

- Dual input K-Type thermocouple temperature tester

5. Differential Digital Manometer

- Dual input differential manometer with 3 selectable units of measure: kPa, mBar, inH₂O, and .001inH₂O
- Tightest test: check for pressure leaks in valves, fittings, and switches with an elapsed time reference

3-YEAR
LIMITED
WARRANTY



Turn over for technical information and accessory part numbers.

NOTE: When selecting oil as fuel be sure to use the optional oil filter or reading could become erratic. Order item A773.

**The
Value
Leader™**

712 FEATURES

- Easy to use
- Large, easy-to-read display
- Store up to 50 data sets; Timed logging 400 sets
- Single log mode: CO, temp., pressure logging
- PC interface
- IR printer port
- Protective rubber boot included

712 ACCESSORIES

CO Sensor, Oxygen Sensor, Protective Boot, Stack Probe, PVC Tubing, Water/filter trap on Stack Probe, Shoulder Strap Carrying Case, Spare Particle Filters, AC/DC Adapter, Rechargeable Batteries

712 OPTIONAL ACCESSORIES

A740 IR Printer

A767 IRDA Adapter for Data Logging

A773 Sulfur Filter

A740 Infrared Printer

- Easy to use
- Battery operated
- Self test facility
- Adjustable contrast
- Manual paper feed
- Maximum transmitting distance 16" (45cm)
- Compatible with most other combustion analyzers



3.0" w
x 6.0 h
x 1.75" d

3-YEAR
LIMITED
WARRANTY



712 Flue Gas Analyzer

TECHNICAL SPECIFICATIONS AND ACCESSORIES

Temperature Measurement

Range	-40° to 1472°, or -40° to 800°C
Resolution	1°F or C
Accuracy (K-type)	±0.3%, ±2°F or ±1°C

Draft/Pressure Measurement & Tightness Test

Selectable Ranges	mBar, kPa, and inH ₂ O
Ranges	-150 mBar to +150 mBar -15 kPa to +15 kPa -60 inH ₂ O to +60 in H ₂ O
Resolution	.001inH ₂ O (0.01mBar)
Accuracy	±0/5% fsd

Gross/Net Efficiency

Range	0 to 100%
Resolution	0.1%

Oxygen (O₂) Measurement

Range	0 to 25%
Resolution	0.1%
Accuracy	±0.3%

Carbon Monoxide (CO) Measurement

Range	0 to 10,000 ppm
Resolution	1 ppm
Accuracy	±5 ppm or 5%, whichever is greater

Carbon Dioxide (CO₂)

Range	0 to 25%
Resolution	0.1%
Accuracy	Calculated

CO/CO₂ Ratio

Range	0 to 0.999
Resolution	0.001
Accuracy	Calculated

Instrument Specifications

Operating Temperature Range	14° to 122°F (-10° to 50°C)
Battery	Rechargeable Ni-MH, >6 Hour Life
Charger Input Voltage	115V or 230V : 50/60 Hz AC
Fuels	Natural Gas, LPG, Light Oil, Heavy Oil
Display	Backlit LCD
Data Storage	50 sets of readings
Data Logging	400 sets of readings in log mode 150 sets of readings in single log mode
Time & Date	24 Hour Real Time Clock
Dimensions	200mm x 90mm x 60mm
Weight	500g
Exhaust	Safety Spigot
Conforms To:	BS7927 (and the draft BS7967)

ACCESSORIES

Standard

Gas Valve Adapter	A611
Adapter Tubing	A791
Pressure Tubing	A774
(2) 1/4 barb to 1/8 NPT	A603
Flue Probe w/K-type	A770
K-Type Temperature Probe	GK11M
In-Line Filter Complete	A762
Mini Pump Protection Filter Assembly	A763
Battery Charger	A766
Protective Boot	A765
Soft Carrying Case	A768
Exhaust Spigot	A764
(2) Static Tips	A776

Optional

Infrared Printer	A740
PC Software	A772
IRDA-RS232C Adapter	A767
Filter for A762 (5 pack)	A762F
20 Foot Flue Gas Analyzer Probe	A770-20
Replacement Printer Paper (2 rolls)	A746
Oil Filter	A773

**NOTE: When selecting oil as fuel be sure to use the optional oil filter or reading could become erratic.
Order item A773.**

Test Products International, Inc.
Headquarters:
9615 SW Allen Blvd.
Beaverton, OR 97005
USA
503-520-9197
Fax: 503-520-1225
email:
info@tpi-thevalueleader.com

Test Products International, Ltd.
342 Bronte St. South
Unit 9
Milton, Ontario L9T
5B7
Canada
905-693-8558
Fax: 905-693-0888
email:
info@tpicanada.com

Test Products International UK Ltd.
Longley House, East Park
Crawley, West Sussex
RH10 6AP England
Tel: +44 (0)1293 561212
Fax: +44 (0)1293813465
contactus@tpieurope.com



Distributed By:

To learn about the entire line of TPI products visit:

www.tpi-thevalueleader.com

L 712-0606
Copyright © 2006 Test Products International, Inc.