

265 Clamp-On Tester with Frequency and Capacitance

APPLICATIONS

Test start and run capacitors

Measure motor run current

Measure heat anticipator current

Determine thermocouple voltage

Test line and control voltages

Measure heating element resistance

Measure and adjust variable frequency drives

OFF(0) **701 265**

Shown Actual Size: 8" x 3"

Why pay more?

Perfect for tight, narrow, spaces...

The new TPI 265 with slim jaw and body is ideal for cramped work areas and crowded electrical panels.

Features

- Slim jaw and body design for use in crowded electrical panels
- 4,000 count display
- Capacitance range up to 4,000 microfards to test run and start capicitors
- 0.1 DC millivolt resolution to accurately measure thermocouples and use optional adapters
- 0.01 AC Amp resolution to measure heat anticipator current
- Frequency measurement capability
- AC/DC volts up to 600V and AC Amps up to 400A
- Diode, resistance, and audible continuity ranges

ALL THESE PLUS!!

- · Auto / manual ranging
- · Data hold
- Auto power off
- · CAT III 600V rated





265 Clamp-On Tester General Features and Specifications

TPI offers a complete line of...

CO, Combustibles & Combustion (CEA)

Refrigerant Leak Detectors

Digital Manometers

Temperature Contact
& IR Instruments

IAQ: Air Flow / Humidity

Handheld Oscilloscope

Digital Multimeters & Clamp-on Meters

Accessories & Kits

Test Products International, Inc.

Headquarters: 9615 SW Allen Blvd. Beaverton, OR 97005 USA 503-520-9197

Fax: 503-520-1225 email:

info@tpi-thevalueleader.com

Test Products International, Ltd.

342 Bronte St. South Unit 9

Milton, Ontario L9T

5B7 Canada

905-693-8558

Fax: 905-693-0888

email: info@tpicanada.com

Test Products International UK Ltd.

Longley House, East Park Crawley, West Sussex RH10 6AP England Tel: +44 (0)1293 561212 Fax: +44 (0)1293813465 contactus@tpieurope.com

Instrument Specifications	
Basic DC Accuracy:	0.5%
DC Voltage (maximum):	600V
Resolution (maximum):	0.1mV
AC Voltage (maximum):	600V
Resolution (maximum):	0.1mV
AC Amps (maximum):	400A
Resolution (maximum):	0.01A
Resistance (maximum):	$40 extsf{M} oldsymbol{\Omega}$
Resolution (maximum):	$0.1oldsymbol{\Omega}$
Frequency (maximum):	400MHz
Resolution (maximum):	0.001KHz
Capacitance (maximum):	4,000μF
Resolution (maximum):	0.001nF
Diode:	Test Current Max 1.5mA
Continuity:	Buzzer sounds at <approx. <math="">35\Omega Response time; $50ms$</approx.>

Overall Dimensions:	8" x 1.5" x 3.0" (203 x 38.1 x 76.2mm)
Weight:	.6 lbs (272g)
Standard Accessories	
A040	Standard test lead set
A265	Soft Carrying Pouch
Optional Accessories	
A202	Line Splitter
A771	Carbon Monoxide Adapter
A620	Pressure Adapter
TLS2000RB	Deluxe Test Lead Kit
A301	Single Input Temperature Adapter
A312	Dual Input Temperature Adapter
A213	Microamp Adapter

Distributed By:

Agency Approval:



To learn about the entire line of TPI products visit:

www.tpi-thevalueleader.com

Copyright © 2006 Test Products International, Inc. L 265- 1106

265

Will the 265 measure temperature?

The 265 has the capability to be used with the A301 single input or A312 dual input K- type adapters to measure temperature.

Are any other adapters available for the 265?

Yes, the 265 can be used wit the A771 to measure carbon monoxide and the A620 to measure pressure.

Can I use the 265 to troubleshoot variable speed motors?

The 265 has the capability to measure frequency making set up and troubleshooting variable speed motors easy.

Is it possible to measure heat anticipator current with the 265?

The 265 has a 40A range with 0.01A resolution, which is ideal for measuring heat anticipator and small motor current.

Can I test the run and start capacitors on motors?

The 265 has the ability to measure capacitors up to 4,000 microfarads in size.

How do I measure AC Amps on a device with a power cord?

To measure AC amps a single wire must be isolated. The A202 line splitter makes this easy without damaging the power cord.